

# Disboxid 948 Color-Chips

Plastic chips/glimmer for the individual surface design of Caparol floor coatings



## Product Description

Field of Application	Plastic chips/glimmer for interspersation in floor coatings, creating an individual surface design.
Material Base / Vehicle	Coloured flakes
Packaging/Package Size	1 kg carton
Colours	Standard colors: white, black, light gray, yellow, red, light blue Especially for the FloorColor plus Collection: Murano C1 to C4, Sierra C1 and C2, Levant C1 and C2, Biscay C1 and C2, Trentino C1 and C2, glimmer gold and silver

## Application

Suitable Substrates	Freshly applied, smooth floor coatings based on epoxy or polyurethane resin. If necessary, deareate with a spiked roller before sprinkling with coloured chips. The formation of skin must not have started when bringing in the chips, otherwise no sufficient inclusion is possible. Suitable for all Caparol floor coatings. ColorChips must not be applied in ESD-, Antistatic- or WHG-(german water protection act) systems.
Mixing Ratio	All colors can be mixed in any desired mixing ratio.
Method of Application	Apply ColorChips with a hopper gun (nozzle size: 10mm) with approx. 2 bar intermittently on the surface. Process the surface uniformly by circular movement. In case of manual appliance, throw small amounts up and let them fall into the area. Avoid material accumulation in order to achieve a uniform appearance.
Consumption	For an open decorative image use 20-40 g/m <sup>2</sup> . Depending on the shade, higher consumption can lead to an uneven surface appearance and to a superposition of ColorChips.
Waiting Time	After an adequate waiting period seal the worked interior surface with Disbopur 458 PU-AquaSiegel or with Disboxid 422 E.MI ClearCoat according to technical information. Use Disbothan 446 PU-Klarschicht for the exteriors.

## Advice

Please Note (Status as at Date of Publication)	Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. Do not allow into drains, water courses or soils.
Disposal	Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local authorities. Particular attention should be paid to removing wastage from site in compliance with standard construction site procedures. In Germany: Only completely emptied packaging should be given for recycling. Dispose remnants as mixed construction and demolition site waste.
Further Details	See Safety Data Sheet (MSDS). Follow the application recommendation and advice for care and maintenance while applying our products.
Customer Service Centre	Tel.: +49 6154 71-71710 Fax: +49 6154 71-71711 e-mail: kundenservicecenter@caparol.de  International Distribution: Please see <a href="http://www.caparol.com">www.caparol.com</a>

## Technical Information No.948 · Issue: July 2017

All suggestions and application instructions herein are based on our latest technical experience. Due to the wide variety of individual project conditions, we cannot be held responsible for their content. These instructions do not release the purchaser/ applicator from his responsibility to determine the suitability of the product in consideration of the project characteristics. These instructions are to be considered void when a new edition is released. Our general conditions of sale and delivery in their latest edition apply. This document is a translation of our German Technical Information No.948 · Disboxid 948 Color-Chips · Issued: April 2013

**DISBON GmbH** · Roszdoerfer Strasse 50 · D-64372 Ober-Ramstadt · Phone +49 6154 71-71719 · Fax +49 6154 71-71008 · Internet [www.disbon.com](http://www.disbon.com)