

Capatect PS-Insulation Board 034 Dalmatiner 160/161/162



Technical Data

Specific use(s)	Facade insulation board
Thermal conductivity	0,034 W/(m · K) in accordance to DIN 4108
Thickness	10 – 300 mm
Dimensions	1000 x 500 mm

Components

Produktcode/GISCODE	no Giscode
VOC-contentt in accordance to RL 2004/42/EG	0 %
VOC-cpntent LEED [less water]	<1 g/l
Lead, Cadmium, Chrome VI *	Not contained
Halogenated propellants *	Not contained
Hexabromcyclododecane (HBCD)	Not contained
SVHC >0,1% - Substances of Very High Concern (*not contained in the formulation)	Not contained

Environmental labels

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

no.	Application site	Product Type	Considered substances / aspects	QS 1	QS 2	QS 3	QS 4
40	Synthetic insulating materials for buildings and building services	PS/XPS/PUR insulating products, flexible building technology insulation (rubber and PE)	Halogenated propellants	Yes	Yes	Yes	Yes
41	Synthetic insulating Materials (building and building services incl. heating and cooling surfaces)	PS/XPS, PUR/PIR, Resol panels	Flame retardant Hexabromocyclo-decane (HBCD)	Yes	Yes	Yes	Yes

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)	Façade product (no requirements)
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)	Façade product (no requirements)
Product Category	No categorie applicable
VOC-limit	---
Limit fulfilled	---
Recyclinganteil	not contained
Production site	DAW SE Roßdörfer Straße 50 DE-64372 Ober-Ramstadt