Capatect-Klebe-und Armierungsmasse 186M



Technical data

Specific use(s)CementDensity1,40 g/cm3Consumption1,5 - 7 kg/m2Gloss levelMatt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE	ZP1; ZP1
Declaration of ingredients	Cement mortar with hydrated lime
Preservation agents	not contained
VOC content in accordance with	< 0.1 %
Directive 2004/42/EC	< 1 g/l
VOC content LEED [less water]	1 g/l
Solvent and plasticiser-free in	yes
accordance with VdL- RL 01	
Water-dilutable in accordance with	yes
2004/42/EC (Decopaint)	
Lead, cadmium, chromium VI *	not contained
SVHC >0,1% - Substances of Very High	not contained
Concern	
(* not contained in the formulation)	

Environmental labels

Sustainability Data Sheet Print Date: 30.06.2023 Revision Date: 30.06.2023

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.

Caparol Farben Lacke Bautenschutz GmbH · Roßdörfer Straße · DE-64372 Ober-Ramstadt · Telephone +496154710 · Telefax +496154711391 · ·

Building certifications - DGNB

No.	Application site	Product Type	Considered	QS 1	QS 2	QS 3	QS 4
			substances /				
			aspects				
5	Coating materials for exterior mineral	Currently, just decorative paints and	VOC	Yes	Yes	Yes	Yes
	surfaces such as concrete, masonry,	dispersion insulation adhesive are					
	mineral mortar and filler, plaster,	taken into account					
	ETICS, wallpaper (façade wallpaper),						
	plasterboard, etc.						

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials) LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)				
Product category VOC limit Limit fulfilled	50 g/l			
Recycling share	not contained			
Production site	DAW SE- Ober-Ramstadt Roßdörfer Straße 50 DE-64372 Ober-Ramstadt			

Building certifications - Assessment System NaWoh

Assessment System Sustainable Housing suitable Constructions (NaWoh) v3.1

Sustainability Data Sheet Print Date: 30.06.2023 Revision Date: 30.06.2023

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.

Caparol Farben Lacke Bautenschutz GmbH · Roßdörfer Straße · DE-64372 Ober-Ramstadt · Telephone +496154710 · Telefax +496154711391 · ·