Capatect ThermoSan Fassadenputz NQG K15



Technical data

Specific use(s) Water-borne coatings Density 1,45 g/cm3 Consumption 1,7 - 3,3 kg/m2

Gloss level Matt (in accordance with DIN EN 13300)

Components

Product Code/GISCODE M-SF01F; BSW50

VOC content in accordance with < 1 % Directive 2004/42/EC < 20 g/l

VOC content LEED [less water] 20 g/l Water-dilutable in accordance with

2004/42/EC (Decopaint)

Film protection contained (active substance complies with (EU) no. 528/2012)

Lead, cadmium, chromium VI * (* not contained in the formulation)

not contained

Environmental labels

This data sheet has been compiled based on state-of-the-art technology and our experience. However, in light of the wide range of requirements regarding buildings certifications, the buyer/user remains personally responsible for checking that our assessment is suitable for the intended certification system and its respective requirements. This data sheet is only valid in its latest version and in combination with the current Technical Information and the Material Safety Data Sheet. Please refer to our website to check the up-to-dateness of this version, if necessary.

Building certifications - DGNB

Suitable according to DGNB criteria ENV1.2 (System version 2018 and 2015)

No.	Application site	Product Type	Considered	QS 1	QS 2	QS 3	QS 4
			substances /				
			aspects				
5	Coating materials for exterior mineral	Currently, just decorative paints and	VOC	Yes	Yes	Yes	Yes
	surfaces such as concrete, masonry,	dispersion insulation adhesive are					
	mineral mortar and filler, plaster,	taken into account					
	ETICS, wallpaper (façade wallpaper),						
	plasterboard, etc.						
31	Products with film preservation and	Exterior plasters, façade coatings	Biocides (product	Yes	Yes	Yes	Yes
	good streated with biocides	,floor coverings made of wool/natural	type 7 and 9 in				
		fibres, wood glazes with film	accordance with				
		preservation	528/2012/EC:Preserv				
			atives for				
			construction				
			materials) e.g.				
			algicides, fungicides,				
			moth repellents				

Building certifications - LEED

LEED v.4 (EQ CREDIT: Low emitting materials)
LEED 2009 (IEQ4.1/ IEQ4.2/ IEQ4.3)

Façade product (no requirements)

(4.3) fulfilled

Product category VOC limit Limit fulfilled

flat topcoat 50 g/l yes

Recycling share

not contained

Production site

DAW SE- Ober-Ramstadt Roßdörfer Straße 50 DE-64372 Ober-Ramstadt

Building certifications - Assessment System NaWoh